

		Status	Door	Buttons	CH
		OFF	Open	P2+P3	42
Menu	Parameters	Machine status	Door	Buttons	Code
Menu 12	Temperature, thermostop, dosage, etc.	OFF	Open	P2+P3	12
Menu 35	SW code, drain pump, softener, etc.	OFF	Open	P2+P3	35
Menu 42 *	All parameters + cycles				

MENU 35 (2)				
Parameter		Default		
			SW 01	SW
<u>CS</u>	Software code	Machine depending	5	
<u>So</u>	Softener	On/Off	OFF	
<u>dP</u>	Drain pump	On/Off	OFF	
<u>PH</u>	Preheating	On/Off	OFF	

MENU 12 (1)				
Parameter		Default		
			SW 05	SW
<u>b</u>	Boiler temperature	°C	78	
<u>t</u>	Tank temperature	°C	60	
<u>th</u>	Thermostop	On/Off	ON	
<u>ES</u>	Energy Saving	On/Off	OFF	
<u>AA</u>	Autostart self-enabling	On/Off	OFF	
<u>dH</u>	Cycles for softener regeneration message	N°	99	
<u>dt</u>	Detergent pump setting time	Sec.	05	
<u>bl</u>	Rinse aid pump setting time	Sec.	03	
<u>dn</u>	Detergent pump priming	On/Off	-	
<u>bn</u>	Rinse aid pump priming	On/Off	-	

MENU 42 (3)				
Label	Parameter	Unit	Default (FW031 - SW ??)	
t	Max. tank temperature setting (max. 75°C)	°C		
r C	Heating in parallel mode	on/off		
d r	Drain program enable	on/off		
d A	Auto dR enabling	on/off		
E t	Energy saving (off, 5°C -30°C)	°C		
L C	Short wash cycle lenght	sec.		
L n	Medium wash cycle lenght	sec.		
L L	Long wash cycle lenght	sec.		
L 3				
t r	Rinse lenght	sec.		
r P	Rinse leght extension with softener	sec.		
P 1	Wash pause	sec.		
P 2	Rinse delay for drain, after wash	sec.		
S L	Drain length	sec.		
r E	Regeneration time	min.		
r r	Resin rinse	sec.		
S F	Final drain	sec.		
S r	Drain time for regeneration	50		
t t	Filling time out	sec. (x10)		
C b				
C t				
d F	Factory reset	no/yes		